

**QUESTIONNAIRE FOR TRAILER, PLATFORM, RAMP, 12-TON**

(To be completed and returned with bid)

MAKE BetterBuilt MODEL PH2722DT-A

EMPTY WEIGHT 6,000 Lbs. GVWR 30,000

LENGTH (OVERALL) 32' 6"

PLATFORM: Length 21' 6" Width 102"  
Deck height 32" Road clearance 21"  
Floor material Oak Thickness 2"

BEAVERTAIL: Length 6'

RAMPS: Length 6' Width 24"  
Min. Center Gap 32" inches Max Center Gap 49" inches

***Describe Ramp Spring Assist Design:***

Dual Compression

Can ramps be raised/lowered with one hand by average adult exerting minimal pressure? Yes

LOADING ANGLE: 10 Degrees

SUSPENSION: Type Dexter Capacity 24,000 Lbs.  
Axle capacity, each 12,000 Lbs.

TIRES: Size 235 x 16 Load range G Type Road Tread

***BRAKES: Air*** 2 ***? Anti-lock*** 1 ***? Size:***

12 1/4 x 5"

SERVICE LITERATURE (List title and manufacturer's part number for each manual to be furnished):

Operators Manual  
Dexter Axle Manual

WARRANTY (Describe): 12 Month Complete

GENERAL: Where is unit manufactured? Double Springs, AL  
 When will current production period end? September 30, 2006  
 What is model number of the succeeding unit? PH2722DT-A  
 How many authorized dealers in South Carolina? 2  
 Does this unit meet full OSHA requirements? Yes

*QUOTATION*

Base 12 ton Platform Trailer per specifications ..... \$ 12,342.00

**Add or Deduct for the following options:**

Electric Winch, 15,000 lb. Line pull capacity per specifications...\$2,000.00

1 ¼ " X 3/16 " serrated bar grating on deck per specifications .... \$ 1,500.00

Electric brakes in lieu of air brakes . Deduct..... -\$1,100.00

**TOTAL BID PER UNIT** ..... \$14,742.00