

STANDARDIZED SPECIFICATIONS (revised 08/11/2016)

The following 14 specifications are applicable if they are listed as “Factory Installed Items” (included in the “Base Price”) or “Option Equipment” (Add or Deduct Pricing). If they are not referenced by the spec item name (example: Tow Package) in the individual vehicle spec, they do not apply. Should it be necessary to deviate from a standard spec, the deviation(s) will be expressly stated within the individual vehicle spec. The individual vehicle spec takes precedence over the standardized vehicle spec. Unless stated otherwise in an individual vehicle’s specification, the following standardized specifications apply:

IMPORTANT NOTICE: Contractors should review purchase orders carefully for items such as drawbar, pin, clip and shank configuration information as well as anything else needing further description for that order as provided in the contract documents. They should notify the governmental entity when needed information is missing. This office will require delivery of all specified items unless the governmental entity provides specific notice of relief from same in writing. **THESE TYPE ITEMS ARE INCLUDED IN THE CONTRACT PRICES!**

AUXILIARY POWER CONNECTION: A factory installed two wire power connection shall be provided in the engine compartment. If the specified connection is NOT offered by the manufacturer, said connection may be installed by an upfitter. Documentation of non-availability from the manufacturer is to be obtained from the manufacturer and included in the bid submittal. The circuit shall be a minimum 5 amp fused with a minimum 14 gauge automotive grade cable. The circuit shall operate with the ignition switch in the “Accessory” or “On” position and shall include one blue wire for ignition and one red wire for accessory. The power connection will allow installation of additional high amperage accessories.

AUXILIARY POWER OUTLET: A factory installed 12 volt single port power outlet shall be provided in the dashboard or front console of the vehicle. The power outlet shall operate independently from other electronic components with a minimum 20 amp circuit. The outlet shall operate with the vehicle ignition switch in the “Off” or “On” position and shall be accessible from the driver’s seat position. If not available from the manufacturer, the auxiliary power outlet may be installed by an up-fitter.

DAYTIME RUNNING LIGHTS: If standard equipment, daytime running lights are to be made inoperable prior to delivery on vehicles purchased by law enforcement entities.

ENGINES – GASOLINE / UNLEADED / E10:

For gasoline powered vehicles and equipment, fuel system components and gasoline engines shall be compatible with E10 ethanol blends, minimum. These engines are to perform as follows:

- No noticeable degradation in vehicle drivability,
- Minimal impact on vehicle operating efficiency (defined to be no more than 10% decrease in fuel economy)
- Maintenance sensors and warning systems are to display normally (example: use of E10 is not to cause the check engine light to display)

NOTICE: The State has transitioned to the E10 Unleaded Fuel Blend. The fuel contracts reflect same.



Remainder of Page Intentionally Left Blank

FLOOR MATS: Unless stated otherwise in the individual vehicle specifications the following applies:

- a) **When floor mats are available through the manufacturer, the mats provided will be either the manufacturer's mats or equal. The equal must meet or exceed the manufacturer's mat fit and quality characteristics. This applies to both carpeted and rubber/vinyl mats. If an equal is being offered, it will be identified in the offer as a dealer installed item.**
- b) Vehicles with carpeted interiors will include high grade factory carpeted floor mats or equal.
- c) Vehicles equipped with vinyl or rubber flooring should be equipped with the factory standard Floor Mat that reduces movement of mats on such flooring material. If a factory standard mat is not available, vehicles equipped with vinyl or rubber flooring should not be delivered with Floor Mats.
- d) In the event required floor mats (listed as a factory installed item in the individual vehicle specification) are not available through the manufacturer; high quality, heavy duty floor mats will be offered and identified in the offer as a dealer installed item. The floor mat type will be the same as that listed in the individual vehicle specification (carpeted).

NOTE: Should a vehicle with carpeted interior specify rubber or vinyl floor mats, the mats will be high quality, heavy duty rubber/vinyl mats. Item A (above) applies.

4 x 4 WHEEL DRIVE PACKAGE - The following items are included:

Transfer Case with Auto Locking Hubs (operator can lock in hubs without leaving the cab)
Factory Skid Plates (minimum set includes transfer case and fuel cell protection)
Locking or Limited Slip Differential or Electronic Traction Control
Suspension – all changes recommended by the manufacturer for 4 x 4 operation.
All Terrain Tires

IMPORTANT DISTINCTION: The State does NOT consider All Wheel Drive (AWD) to be equivalent to Four Wheel Drive (4 x 4). Therefore, AWD will NOT be accepted as a substitute for 4 x 4.

FUEL SYSTEM: For Diesel powered vehicles and equipment, fuel system components and Diesel engines shall be compatible with B20 bio-diesel blends, minimum.

HEAD RESTRAINTS: All outboard seating positions shall have factory installed head restraints via head rests or high back seats. The head restraints shall meet all requirements of U. S. Department of Transportation National Highway Traffic Safety Administration and Federal Motor Vehicle Standards.

NOTE: If head restraints are not available, the contactor shall provide each ordering governmental entity notification from the manufacturer verifying that head restraints are not available. **If head restraints are available from the manufacturer as either a standard or option item, they must be included in the offer and incorporated into the base price of the vehicle.**

MIRRORS – EXTENDED, BREAKAWAY: The primary mirror will be a minimum of 6" x 14". The convex mirror will be a minimum of 5". The purpose of the mirror is to improve the driver's view to the rear when towing and backing.

RADIO NOISE SUPPRESSION: The vehicle is to be used as a governmental fleet vehicle and will have an approximate 150-watt mobile (two-way) radio installed, operating on frequencies designated by the FCC for use in the Public Safety Radio Service (47 CFR 90). The vehicle shall be fully compatible with the above radio installation, and vehicle components and equipment shall not interfere with operation (transmitting or receiving) of the mobile radio.

STEP BAR – ENTRY / EGRESS: On level ground, where the vertical clearance from the ground to door threshold (place where the driver and passenger(s) place their foot when entering the cab) exceeds nineteen inches, a 3 inch diameter step bar shall be installed on both sides of the vehicle so the ground clearance to the bar does not exceed nineteen inches. For vehicles with extended, quad, or crew cabs, an extended or double step bar shall be installed that services entry to and egress from all doors. In all cases, overall manufacturer desired

vehicle ground clearance must be maintained. The bar shall be the type customarily manufactured and marked for this purpose. It may be factory, dealer, or approved up-fitter installed. The step bar shall be a BULLY single, extended, or double step bar, or equal. **For vans and utilities (SUV's)** with steps that exceed nineteen inches, a full running board type step with a platform measuring no less than six inches deep must be installed to allow entry and egress from all side doors (including all doors mounted on drivers side.) A step is not required for rear door access.

Step Bar Color: Black Powder Coated

OEM molded plastic running boards are acceptable (black).

THREE (3) KEYS: Three (3) complete sets of keys to include two (2) remote entry key fobs are to be provided for each vehicle delivered. The cost for same is included in the base price. This requirement applies to all types of key systems (traditional key sets, programmable keys, keys with remote fobs, etc.)

TIRES: Tires will be mounted with black walls turned to the outside. All tire walls with contrasting colors such a white walls, red walls, raised white letters, etc. will be turned to the inside. The buying governmental entity may reject delivery if black walls are not turned to the outside.

TOW PACKAGE ****FACTORY INSTALLED****: Factory installed hitch plus all necessary components to match or exceed the maximum rated towing capacity of vehicle are to be included. Wiring will include everything necessary to hook-up both 4 way and 7way wiring harnesses. Contractor to provide **(at no additional charge)** the drawbar, pin, clip, ball, and shank configuration specified by the owner when each order is placed (example: Dept. of Natural Resources standard configuration unless specified otherwise on their purchase order is as follows: Drawbar w/2" drop, pin, clip, and 2" ball w/ 1" solid shank).

NOTE: **If the drawbar, pin, clip, and shank configuration is inadvertently left off a purchase order, it does not relieve the contractor of the requirement to provide same as specified in the contract documents.**

WINCH: Electric, Front Mount, 9,000 lb. with Roller Fair Lead (5742) and 125' cable, Grill Guard and Mounting Bracket, Warn model XD9000i. **Mounting bracket must not extend down below the height of the front bumper. (May be installed by Dealer or approved Upfitter)**



Remainder of Page Intentionally Left Blank

CC-6: CAB / CHASSIS 37,000 GVWR (DIESEL)

EQUIPMENT: The cab & chassis truck shall be equipped with all standard equipment as specified by the manufacturer for this model, and shall comply with all EPA Emission Standards and all Motor Vehicle Safety Standards as established by the U.S. Department of Transportation regarding the manufacture of motor vehicles.

BRAKES: The truck shall be provided with full ABS air brake equipment for all wheels, with automatic slack adjusters, and with heavy-duty, non-asbestos lining material. The air compressor shall have a capacity of not less than 12 CFM. In addition to all brake equipment already specified or customarily furnished as standard, the truck shall be equipped with a low air pressure indicator or alarm, automatic type moisture remover(s) on each tank, a slack adjuster for each wheel, brake dust shields, dash mounted air pressure gauge. The truck shall be equipped with a spring set, air release rear wheel parking brake. All brake equipment shall conform to the latest regulations of the ICC, and shall be in full compliance with FMVSS 121. Brake chambers and springs on rear axle shall be mounted high enough to provide paver clearance. Brake system air tanks will be mounted to allow adequate clearance above frame rails for truck body installation and provide adequate clearance for PTO assembly and/or drive-shafts on the left or right side. Full anti-lock brake (ABS) system.

CAPACITY: The truck shall have a minimum gross vehicle weight rating (GVWR) of not less than 37,000 lbs. ~~Optional equipment shall be available to order units with an increased CA up to 138 inches.~~ The truck shall have a minimum gross combination weight rating (GCWR) of not less than 60,000 lbs. as bid with Allison 3500 RDS 6-speed transmission.

COLOR: The truck cab, hood and fenders shall be painted standard factory white and sealed with clear coat finish. The frame and running gear shall be painted black. Front bumper may be painted black or gray. (Low or no lead).

DESCRIPTION: The truck shall be a heavy-duty, conventional cab unit with forward tilting hood suitable for use as a dump truck, as well as other applications.

DIMENSIONS: CA: 84 inches minimum. WB: 149 inches minimum. BBC: 96-113 inches. Cab OAH: 88-108 inches. Curb weight: 6,200 lbs. minimum.

ENGINE: The truck engine (diesel) shall be a Cummins ISL9 (8.9L), PACCAR PX-9 rated at not less than 300 SAE gross horsepower and minimum 860 ft. lbs. torque. The air filter shall be a heavy-duty, dry-type with restriction indicator, and with complete ducting for fresh air intake, with Donaldson the preferred manufacturer. The engine shall be complete with heavy-duty oil filter, heavy duty fuel filter/water separator governor, muffler, horizontal exhaust system, vertical tail pipe and guard, and heavy-duty (maximum) cooling system. The cooling system shall be filled with an extended life coolant suitable for this application. The alternator shall be rated at not less than 130 amps. The horizontal exhaust system shall be mounted outside right frame rail and under the cab to provide adequate clearance for PTO assembly and/or drive shafts on the left or right hand side. The vertical tail pipe shall be approximately the same height as the cab with a radius bend at the top of the tail pipe to deflect exhaust away from the cab and installed dump body. The tail pipe and guard shall not interfere with dump body, which is installed 4 inches from back of cab. Additionally, it shall not interfere with raising and lowering the dump body.

FRAME: The truck frame side members shall have dimensions not less than the following: depth - 9.06 inches, width - 3.00 inches, thickness - 0.28 inches, and minimum 80,000 psi with a RBM of not less than 1,275,000.

FRONT AXLE: Minimum 14,000 lbs. The suspension system and springs shall be of adequate capacity to maintain the GWVR and GAWR.

FUEL TANK: Minimum 45 gallon capacity located on right or left hand side, step type.

INTERIOR: Vinyl, gray or black in color.

REAR AXLE: Eaton, Dana-Spicer, or Meritor heavy duty, single-speed, having a maximum load rating of not less than 23,000 pounds. The gear ratios shall be approximately 5.57 to 1. The suspension system and springs shall be of adequate capacity to maintain the GVWR and GAWR. Auxiliary springs rated at 2,250 lbs. per side shall be furnished. The assembled truck shall be capable of achieving 72 mph loaded on level grade. The assembled truck shall be capable of achieving 60 mph fully loaded on 1.1% grade.

STEERING: Power Assist.

TIRES: Front – 12R22.5, load range H, regular steer tread, radial, tubeless, Goodyear G661 or equal. Rear - 12R22.5, load range H, traction lug tread, radial, tubeless, Goodyear G182 or equal.

TRANSMISSION: Allison Model 3500 RDS, minimum 6-speed automatic with standard six (6) bolt SAE PTO opening on left and right side. Pushbutton type transmission shift control shall be mounted in or on the dashboard instrument panel.

WHEELS: Disc type, steel, tubeless, 10-hole, 11 1/4" bolt circle, 8 22/32" bore, 1 9/32" stud hole, stud pilot, heavy-duty, 22.5" x 8.25" x 7/16", 6.62" off-set (nom.) max. load rating not less than 7,000 lbs., color - white, interchangeable at all positions on the vehicle.

FACTORY INSTALLED ITEMS

The following options shall be furnished in addition to, or in place of, the regular standard equipment and will be "Factory Installed", unless otherwise specified.

1. Air-Conditioning
2. AM/FM Radio
3. Automatic moisture ejectors on each air tank
4. Auxiliary Power Connection: (Standard State Specification)
5. Auxiliary Power Outlet: (Standard State Specification)
6. Back-up Alarm (107 db with ID label)
7. Battery, heavy duty, 2 each – Group 31, 625 CCA min., mounted in enclosed battery box


CC-6: CAB / CHASSIS 37,000 GVWR (DIESEL)

8. Brake dust shields
9. Chassis electrical cable and 7-way receptacle connector, Velvac 593084 or equal connector for trailers with anti-lock braking system (may be dealer installed, see description and diagram)
10. Daytime running lights
11. Door Locks, Power, Driver and Passenger
12. Dual quick disconnect, trailer air brake connectors (Glad Hands)
13. Dual 2 Speed (minimum) Windshield Wipers
14. Dual Sun Visors
15. Entry Assist Handles, Left and Right - External
16. Fender Mounted Turn Signals, Amber Front, Red Rear
17. Grill, stationary, with bug screen (installed by OEM approved upfitter)
18. Heavy Duty Air Filter
19. Heavy-Duty, Full Width Front Bumper
20. Horn, Air
21. Mud flaps, front only, black
22. Pintle Hook (may be dealer installed – see description diagram).
23. Power Windows, Driver and Passenger
24. Rectangular West Coast 7" x 16" Breakaway Mirrors and Convex Mirrors, Power, Driver and Passenger
25. Speedometer, Tachometer, Oil Pressure Gauge, Ammeter/Voltmeter, Fuel Gauge, Transmission Temperature Gauge, Water Temperature Gauge, Engine Hour Meter
26. Split bench seat designed to seat driver plus 2 passengers. Headrests or high backs at outside positions. Lap safety belts for all positions and shoulder safety belts at outside positions. Driver's seat includes air-ride controls. Rear seat in extended and crew cab includes headrests at outside positions and lap and shoulder safety belts (if available).
27. Trailer electrical cable, 6-way connector, Velvac 055052 assembly or equal (may be dealer installed, see description diagram)
28. Visible or audible signal to warn operator of low oil pressure and/or high coolant temperature.

CC-6: CAB / CHASSIS 37,000 GVWR (DIESEL)

****NOTE**** If purchaser is NOT using a state contract holder to install the body, the purchaser **MUST** coordinate with the upfitter for the redesigned pintle hook installation*******

PINTLE HOOK: A heavy-duty, 25 ton capacity, suitable for 2 3/8" to 3" pintle eye dimensions. The pintle hook shall be a spring-cushioned, swiveling hook with plunger type latch utilizing a spring-loaded lock pin and mounted below the truck frame, to the rear of the spring shackles. The pintle hook shall be mounted on a 8" structural channel steel that is 18.75 lbs. per ft. Channel entire width shall be reinforced with 6" x 1/2" flat bar backing and each end with 1/2" x 8" x 8" steel plates (minimum). The cross-member shall extend across the entire width of the truck frame. The pintle hook centerline shall be 28-29" from ground level on the truck cab-chassis. See drawing below.



Two (2) heavy-duty, 1" thick safety chain lashing rings, minimum 46,760 lbs. ultimate breaking strength each, Buyers Products B50 or equal, shall be attached to the pintle hook cross-member by two (2), minimum 1/2" x 2" flat bar steel straps seam welded inside of the lashing ring. The brackets or shackles shall accept both 3/8" and 1/2" grab hooks.

A trailer electrical connector bracket shall be attached by welding to the top left side of the pintle hook cross-member. The bracket shall be constructed of 1/4" angle steel.

The pintle hook cross member shall be welded to the truck frame and shall have a 1/4" steel plate mounted on both ends of the cross member to attach to the frame. The steel plates shall be attached using (4) 5/8" Grade 8 bolts per plate, (2) bolts joining each plate to the cross member and (2) bolts joining each plate to the frame. See drawing above.

The installation shall not interfere with dump body installation or operation. The pintle hook mounting method shall be approved by the South Carolina Department of Transportation on a pilot model prior to installation on the remaining trucks.


All welding shall be performed by skilled fabricators possessing a valid American Welding Society (AWS) or American Society of Mechanical Engineers (ASME) structural welding certification. Proof of certification (per individual fabricator) shall be provided prior to award of contract – (may be

CC-6: CAB / CHASSIS 37,000 GVWR (DIESEL)

included w/ bid submittal but must be received no later than five business days after Intent to Award notice is posted – sent to ATTN: Allen Register @ MMO-PO Box 101103, Columbia, SC 29211).

All hardware used in the above installation shall be Grade 8, plated.

TRAILER ELECTRICAL CONNECTOR (STANDARD): The truck shall be equipped with a standard 6-way receptacle connector, equal to and interchangeable with a Velvac 055052 assembly, mounted in the pintle hook cross-member, and wired utilizing a heavy-duty, jacketed, multi-conductor cable. The receptacle shall be connected to the truck wiring system in accordance with the following drawing:




Letter Code	Trailer Color Code
GD - Brake Wire Ground	WHITE
TM - Tail & Marker Lamp	BLACK
S - Stop Lamp	RED
RT - Right Dir. Signal	GREEN
LT - Left Dir. Signal	YELLOW
A - Live Brake Wire	BROWN

TRAILER ELECTRICAL ABS CONNECTOR (STANDARD): In addition to the standard 6-way receptacle, the truck shall be equipped with a standard 7-way electrical receptacle connector for trailers with Anti-lock Braking Systems (ABS). The connector shall be equal to and interchangeable with a Velvac 593084 assembly, mounted in the pintle hook cross member, and

CC-6: CAB / CHASSIS 37,000 GVWR (DIESEL)

wired utilizing a heavy duty, jacketed, multi-conductor cable. The receptacle shall be connected to the truck wiring system in accordance with the following drawing.



Letter Code	Trailer Color Code
GD - Ground Return	WHITE
M - Clearance, Side, & Marker Lamps	BLACK
LT - Left Turn and Hazard Signal	YELLOW
S - Stop Lamp and Anti-Lock Device	RED
RT - Right Turn and Hazard Signal	GREEN
TM - Tail, Rear Clearance Markers	BROWN
A - ABS Power and Auxiliary Circuit	BLUE

Pilot model to be approved prior to subsequent installations.

NON-SKID STEPS: Provide non-skid surface on step treads by application of 3M No-Skid Coating No. EC1420, black, or by another acceptable non-skid surface that is factory installed.

CC-6: CAB / CHASSIS 37,000 GVWR (DIESEL)

ELECTRIC TRAILER BRAKE CONTROLLER (STANDARD): A hand-controlled and automatic solid state electronic trailer brake controller actuator with digital readout, Pilot Model 80550 or equal, shall be installed in the truck, and wired through the trailer electrical connector to operate electric brakes on trailers up to 3 axles in a manner proportional to the braking effort exerted and intended by the driver. Where options are approved for dealer installation (fuel filter, trailer electrical connector, pintle hook, non-skip steps, and trailer brake controller), the inspection of these options may be delayed until after the pilot model truck is delivered to the dealer.

MAINTENANCE: All replaceable filter elements for air, fuel, hydraulics, and engine oil shall be available from at least one of the following U.S. manufacturers: AC, Wix, Donaldson, or Baldwin. Replacement tires and tubes shall be available from at least one of the following U.S. manufacturers: Goodyear, Firestone or General. Replacement or replenishment lubricants required throughout the unit (engine oil, transmission fluid, hydraulic fluid, gear oil, brake fluid, power steering fluid, and grease) shall be available from at least one of the major manufacturers: Shell, Exxon, Texaco, or Citgo. Details concerning the manufacturer and items name or part number for the above maintenance items shall be provided wherever requested on the bid questionnaire.

ACCEPTANCE INSPECTION: All equipment ordered with this request will be subject to acceptance inspection and performance testing upon receipt. The vendor will be notified of any units not delivered in full compliance with the purchase order specifications.

SALES LITERATURE AND SPECIFICATIONS: Each bidder shall attach to his bid illustrated catalog data sheets with manufacturers complete printed specifications covering the class or type of equipment covered by the bid. This material shall show reasonable evidence of having been printed before publication of the bid notice and shall be sufficiently detailed to permit the Department engineers and/or staff to properly evaluate the bid.

GENERAL: The units shall be of the latest design and in current production. They shall be furnished completely assembled, fully serviced, and ready for immediate operation. The right is reserved to reject any and all bids proposing to furnish equipment which, in the opinion of the Department's engineers and/or staff, is not satisfactory for the Department's use in the proposed application.

OPTIONAL EQUIPMENT

The following factory installed options may or may not be ordered. Offers must provide a price for all options or offer as part of the base price. If the option item is "STANDARD" enter "STD" on the line provided for price. **ALL ITEMS SHOULD HAVE A DOLLAR PRICE OR "STD" LISTED. OFFERS WILL NOT BE CONSIDERED IF THE PRICE LINE IS LEFT BLANK.**

ADDS:

1. 120" CA – Increase CA to 120"
2. Body Installation Fee (Charge based on the dealer arranging for bodies to be installed on this cab & chassis from the State contract vendor)
3. Extended Cab ~~(Deletes Air Ride Driver Seat)~~

CC-6: CAB / CHASSIS 37,000 GVWR (DIESEL)

4. Operators Manual
5. Operator Training
6. Repair Technician Training
7. Shop Manual (For all components – CD or DVD Preferred – Specify)

DEDUCTS:

1. Auxiliary Power Outlet: (Standard State Specification)
2. Pintle Hook Assembly

Options requiring the additions of other options as well as those which are included as part of another:



State of South Carolina

Bid

Status: 5500047468 Bid Submitted

Created: 09/22/2016 14:32:15 EST
LINDA BARKSDALE

Last upd: 09/23/2016 08:42:50 EST
LINDA BARKSDALE

Bidder

CAROLINA INTERNATIONAL TRUCKS INC
1619 BLUFF ROAD
COLUMBIA SC 29201

Invitation For Bid

Version: 3

Bid invitation number: 5400011744

Description: STATEWIDE FOR CAB & CHASSIS

Buyer name:

Buyer email:

Buyer phone:

Follow-on document: Contract

Valid From: 11/01/2016

Valid To: 10/31/2018

Estimated award date: 10/13/2016

SCBO catg: Equipment

Bid invitation rules

Bidding procedure: Public bid invitation

Requested price information: Normal price

Timezone: EST

End date/time: 09/26/2016 15:00:00 EST

Bids required for all items? No

Bid may be changed? Yes

Bidder can add items? No

Bid Basic Data

Terms of Payment: net 30 days

Currency: USD United States Dollar

Information from purchaser - header attachment(s)

Description

Vehicle Questionnaire

Solicitation

Amendment #1

Bidder's header attachment(s)

Description

NO BID LETTER

Header attributes

The bidder has read and understands all Amendments.

Bidder Response: Y

1. The Submitter has read and understands the terms and conditions of this solicitation.

Bidder Response: **Yes. I have read and understand the terms and conditions.**

Permitted Values - Yes. I have read and understand the terms and conditions.

2. The offer is in accordance with the terms and conditions of this solicitation.

Bidder Response: **Yes, I am in accordance with the terms and conditions.**

Permitted Values - Yes, I am in accordance with the terms and conditions.

Invitation For Bid

Version: 3

Bid invitation number: 5400011744

Description: STATEWIDE FOR CAB & CHASSIS

ADDS - TOTAL OF ALL ADDSBidder Response: **1,338.00 (United States Dollar)****ADDS - TOTAL ADDS X 0.25**Bidder Response: **335.00 (United States Dollar)****DEDUCT - Auxiliary Power Connection**Bidder Response: **37.00 (United States Dollar)****DEDUCT - AUXILIARY REAR SPRINGS**Bidder Response: **0.01 (United States Dollar)**Comments: **Standard Item - No Charge****DEDUCT - PINTLE HOOK ASSEMBLY**Bidder Response: **1,275.00 (United States Dollar)****DEDUCTS - TOTAL OF ALL DEDUCTS**Bidder Response: **1,312.00 (United States Dollar)****DEDUCTS - TOTAL DEDUCTS X 0.25**Bidder Response: **328.00 (United States Dollar)****EVALUATED AMOUNT - (BASE PRICE) PLUS (TOTAL ADDS X 0.25) MINUS (TOTAL DEDUCTS X 0.25)**Bidder Response: **60,654.00 (United States Dollar)****Specify the Terms of the Warranty for this Vehicle**Bidder Response: **60months/6300hours/175,000miles****Line Number: 0006****CC-6: 37,000 GVWR, Diesel Engine**

Item Category: Material

Vendor Product Number: 7000

Product Category: 07210 - Trucks Cab & Chassis Only

Internal Item Number: 6

Target Quantity of Bid Invitation: 10.00 each

Price: **69,999.00 (United States Dollar) Per 1 each**Delivery Time (Duration): **75 days****Information from purchaser - item tendering text**

CC-6: 33,000 GVWR, Diesel Engine, Std. Cab, 120" CA

Bidder's item attachment(s)

Minority

Insurance

Cover

Workstar

Invitation For Bid

Version: 3

Bid invitation number: 5400011744

Description: STATEWIDE FOR CAB & CHASSIS

Item attributes

Are you entering a bid for this line item? If so, then all remaining attribute questions must be answered. Failure to respond to any attribute question may result in your bid being determined non-responsive.

Bidder Response: **Y**

Questionnaire - Year

Bidder Response: **2018**

Questionnaire - Make

Bidder Response: **International**

Questionnaire - Model

Bidder Response: **Workstar**

Questionnaire - Series

Bidder Response: **7000**

Questionnaire - Engine (Cylinder)

Bidder Response: **6**

Questionnaire - Engine (Liter)

Bidder Response: **8.9**

QUESTIONNAIRE - STANDARD FACTORY COLORS EXTERIOR

Bidder Response: **white, red, black, blue, orange**

QUESTIONNAIRE - STANDARD FACTORY COLORS - INTERIOR

Bidder Response: **gray**

INDICATE DELIVERY TIME DAYS ARO

Bidder Response: **75 Days**

ADD - BODY INSTALLATION FEE FOR ARRANGEMENT OF BODIES TO BE INSTALLED BY STATE CONTRACT VENDOR

Bidder Response: **200.00 (United States Dollar)**

ADD - INCREASE CA TO 120" (FROM 84")

Bidder Response: **0.01 (United States Dollar)**Comments: **Standard Item - No Charge**

Add - Auxiliary Power Connection

Bidder Response: **0.01 (United States Dollar)**Comments: **Standard Item - No Charge**

ADD - Extended Cab (List Model)

Bidder Response: **2,548.00 (United States Dollar)**

ADD - OPERATORS MANUAL

Bidder Response: **0.01 (United States Dollar)**

Invitation For Bid

Version: 3

Bid invitation number: 5400011744

Description: STATEWIDE FOR CAB & CHASSIS

Comments: **Standard Item - No Charge**

ADD - OPERATOR TRAINING

Bidder Response: **0.01 (United States Dollar)**Comments: **Standard Item - No Charge**

ADD - REPAIR TECHNICIAN TRAINING

Bidder Response: **0.01 (United States Dollar)**Comments: **Standard Item - No Charge**

ADD - SHOP MANUAL (FOR ALL COMPONENTS - CD OR DVD PREFERRED SPECIFY)

Bidder Response: **0.01 (United States Dollar)**Comments: **Standard Item - No Charge**

ADDS - TOTAL OF ALL ADDS

Bidder Response: **2,748.00 (United States Dollar)**

ADDS - TOTAL ADDS X 0.25

Bidder Response: **687.00 (United States Dollar)**

DEDUCT - Auxiliary Power Connection

Bidder Response: **36.00 (United States Dollar)**

DEDUCT - PINTLE HOOK ASSEMBLY

Bidder Response: **1,275.00 (United States Dollar)**

DEDUCTS - TOTAL OF ALL DEDUCTS

Bidder Response: **1,311.00 (United States Dollar)**

DEDUCTS - TOTAL DEDUCTS X 0.25

Bidder Response: **328.00 (United States Dollar)**

EVALUATED AMOUNT - (BASE PRICE) PLUS (TOTAL ADDS X 0.25) MINUS (TOTAL DEDUCTS X 0.25)

Bidder Response: **70,358.00 (United States Dollar)**

Specify the Terms of the Warranty for this Vehicle

Bidder Response: **60months/6300hours/175000miles**